



SPECIFICATION	VALUE
NO. OF PHASE	4
AMPS/PHASE	0.28
RESISTANCE/PHASE(Ohms)@20°C	85±7%
INDUCTANCE/PHASE(mH)@1KHz	32.9±20%
HOLDING TORQUE(mN.m)[lb-in]	44.1[0.39]
LINEAR TRAVEL/STEP(mm)	0.0208
LEAD(mm)	0.5
STEP ANGLE(°)	15.0±7%
PULL-IN RATE(PPS)	420 MIN
PULL-IN TORQUE(mN.m)@100PPS	10.78
DETENT TORQUE(mN.m)	<12.74
ROTOR INERTIA(g-cm ²)	7.5
WEIGHT(g)[lb]	89.7[0.20]
LIFE(h)@20°C 100PPS	3000 MIN
INSULATION RESISTANCE(MΩ) @DC 500V	100
TEMPERATURE RISE:MAX.75°C	
AMBIENT TEMPERATURE -10°C~40°C[14°F~104°F]	
INSULATION CLASS E 120°C[248°F]	
DIELECTRIC STRENGTH 650±50VAC FOR 2SEC.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE)	

FULL STEP 4 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

PIN NO.	WIRE COLOR	STEP			
		1	2	3	4
1	YEL	-			-
2	BLK			-	-
3	RED	+	+	+	+
4	RED	+	+	+	+
5	ORG	-	-		
6	BLU			-	-



mm	APVD	5.15.2019
UNIT	CHKD	
2:1	DRN	
SCALE	SIGNATURE	DATE

PM STEPPER MOTOR

35LN24M01-122