



15W Ultra Slim Step Shape DIN Rail

HDR-15 series



■ Features

- Ultra slim design with 17.5mm(1SU) width
- Universal input 85~264VAC(277VAC operational)
- No load power consumption<0.3W
- Isolation class II
- Pass LPS (Limited power source)
- DC output voltage adjustable
- Protections : Short circuit / Overload / Over voltage
- Cooling by free air convection (working temperature:-30~+70°C)
- DIN rail TS-35/7.5 or 15 mountable
- Over voltage category III
- LED indicator for power on
- 3 years warranty

■ Applications

- Household control system
- Building automation
- Industrial control system
- Factory automation
- Electro-mechanical apparatus

■ Description

HDR-15 is one economical ultra slim 15W DIN rail power supply series, adapt to be installed on TS-35/7.5 or TS-35/15 mounting rails. The body is designed 17.5mm(1SU) in width, which allows space saving inside the cabinets. The entire series adopts the full range AC input from 85VAC to 264VAC(277VAC operational) and conforms to BS EN/EN61000-3-2, the norm the European Union regulates for harmonic current.

HDR-15 is designed with plastic housing that it can effectively prevent user from electric hazards. With working efficiency up to 87%, the entire series can operate at the ambient temperature between -30°C and 70°C under air convection. The complete protection functions and relevant certificates for home automations and industrial control apparatus (IEC62368-1, UL508, UL62368-1, BS EN/EN61558-2-16) make HDR-15 a very competitive power supply solution for household and industrial applications.

■ Model Encoding

HDR - 15 - 12

Output voltage

Rated wattage

Series name

SPECIFICATION


MODEL		HDR-15-5		HDR-15-12		HDR-15-15		HDR-15-24		HDR-15-48	
OUTPUT	DC VOLTAGE	5V		12V		15V		24V		48V	
	RATED CURRENT	2.4A		1.25A		1A		0.63A		0.32A	
	CURRENT RANGE	0 ~ 2.4A		0 ~ 1.25A		0 ~ 1A		0 ~ 0.63A		0 ~ 0.32A	
	RATED POWER	12W		15W		15W		15.2W		15.4W	
	RIPPLE & NOISE (max.) Note.2	80mVp-p		120mVp-p		120mVp-p		150mVp-p		240mVp-p	
	VOLTAGE ADJ. RANGE	4.5 ~ 5.5V		10.8 ~ 13.8V		13.5 ~ 18V		21.6 ~ 29V		43.2 ~ 55.2V	
	VOLTAGE TOLERANCE Note.3	± 2.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%	
	LINE REGULATION	± 1.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%	
	LOAD REGULATION	± 1.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%	
	SETUP, RISE TIME	2000ms, 80ms/230VAC 2000ms, 80ms/115VAC at full load									
	HOLD UP TIME (Typ.)	30ms/230VAC 12ms/115VAC at full load									
INPUT	VOLTAGE RANGE	85 ~ 264VAC (277VAC operational) 120 ~ 370VDC (390VDC operational)									
	FREQUENCY RANGE	47 ~ 63Hz									
	EFFICIENCY (Typ.)	80%		85%		85.5%		86%		87%	
	AC CURRENT (Typ.)	0.5A/115VAC 0.25A/230VAC									
	INRUSH CURRENT (Typ.)	COLD START 25A/115VAC 45A/230VAC									
PROTECTION	OVERLOAD	110 ~ 145% rated output power									
		Hiccup mode when output voltage <50%, recovers automatically after fault condition is removed									
		Constant current limiting within 50% ~ 100% rated output voltage, recovers automatically after fault condition is removed									
	OVER VOLTAGE	5.75 ~ 6.75V		14.2 ~ 16.2V		18.8 ~ 22.5V		30 ~ 36V		56.5 ~ 64.8V	
ENVIRONMENT	WORKING TEMP.	-30 ~ +70℃ (Refer to "Derating Curve")									
	WORKING HUMIDITY	20 ~ 90% RH non-condensing									
	STORAGE TEMP., HUMIDITY	-40 ~ +85℃, 10 ~ 95% RH non-condensing									
	TEMP. COEFFICIENT	± 0.03%/℃ (0 ~ 50℃) RH non-condensing									
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes; Mounting: Compliance to IEC60068-2-6									
	OPERATING ALTITUDE	2000 meters									
	OVER VOLTAGE CATEGORY	III ; According to EN61558, EN50178, EN60664-1, EN62477-1 ; altitude up to 2000 meters									
SAFETY & EMC (Note 4)	SAFETY STANDARDS	UL62368-1, UL508, TUV BS EN/EN61558-2-16, BS EN/EN61558-1, IEC62368-1, EAC TP TC 004, BSMI CNS14336-1 approved; Design refer to TUV BS EN/EN62368-1									
	WITHSTAND VOLTAGE	I/P-O/P:4KVAC									
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25℃/ 70% RH									
	EMC EMISSION	Parameter	Standard				Test Level / Note				
		Conducted	BS EN/EN55032(CISPR32), CNS13438				Class B				
		Radiated	BS EN/EN55032(CISPR32), CNS13438				Class B				
		Harmonic Current	BS EN/EN61000-3-2				Class A				
		Voltage Flicker	BS EN/EN61000-3-3				-----				
	EMC IMMUNITY	BS EN/EN55024, BS EN/EN55035, BS EN/EN61000-6-2, BS EN/EN61204-3									
		Parameter	Standard				Test Level /Note				
		ESD	BS EN/EN61000-4-2				Level 3, 8KV air; Level 2, 4KV contact, criteria A				
		Radiated Susceptibility	BS EN/EN61000-4-3				Level 3, criteria A				
		EFT/Burest	BS EN/EN61000-4-4				Level 3, criteria A				
		Surge	BS EN/EN61000-4-5				Level 4, 2KV/L-N, criteria A				
		Conducted	BS EN/EN61000-4-6				Level 3, criteria A				
		Magnetic Field	BS EN/EN61000-4-8				Level 4, criteria A				
		Voltage Dips and interruptions	BS EN/EN61000-4-11				>95% dip 0. 5 periods, 30% dip 25 periods, >95% interruptions 250 periods				
OTHERS	MTBF	1166K hrs min. MIL-HDBK-217F (25℃)									
	DIMENSION	17.5*90*54.5mm (W*H*D)									
	PACKING	78g;160pcs/13.5Kg/1.14CUFT									
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μf & 47μf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to “EMI testing of component power supplies.” (as available on http://www.meanwell.com) 5. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft). ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx										




15W Ultra Slim Step Shape DIN Rail

HDR-15 series


■ Block Diagram



■ Derating Curve



■ Output Derating VS Input Voltage







15W Ultra Slim Step Shape DIN Rail

HDR-15 series

Mechanical Specification

(Unit: mm , tolerance $\pm 0.5\text{mm}$)



ADMISSIBLE DIN-RAIL: TS35/7.5 OR TS35/15

Terminal Pin No. Assignment

Pin No.	Assignment	Pin No.	Assignment
1	+V	3	AC/N
2	-V	4	AC/L

Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>